

Shrink Film Packaging Machine

«QUICKPAC»



Operation panel with thermostat, speed control of conveyor belt and a digital display and control of sealing time

compact • efficient • reliable • ever lasting • economic price

Typical installations:

This proofed semi automatic shrink film packaging machine in compact design will pack all kind of products fully wrapped into shrink film. Even the basic machine will be equipped with all-in features to allow fast and economical packaging.

Basic equipment:

- machine standing on lockable castors for mobile use and easy transport handling
- magnetic sealing jaw locking for continuous sealing results
- impulse controlled sealing with infinitely adjustable sealing and cooling time
- on request with cut sealing system for PP co-extruded shrink films or with T-shaped sealing wire for PE film up to approx. 80 my (produces a strong and safe sealing seam at the same time, when the film is cut)
- shrinking air circulation with infinitely adjustable shrinking temperature
- infinitely adjustable speed of the conveyor belt
- annexed cooling extension to store packaged products and to cool down the shrink film

Extras and options:

- Rotating conveyor bars for neat shrunk bottoms of your package
- Distance of conveyor bars 25 mm instead of 37 mm
- Teflon net-belt to avoid passing smaller parts between bars or to wrap packs with legs etc.
- Annexed roller conveyor of 1 m length

Technical dates:

	QUICKPAC - 44	QUICKPAC - 46	QUICKPAC - 200
Sealing frame:	400 x 400 mm	600 x 400 mm	400 x 400mm
Width of conveyor belt:	340 mm	340 mm	340 mm
Passage in height of shrinking tunnel:	150 mm	150 mm	200 mm
Heating ca-pacity:	4 kW	4 kW	4 kW
Electric power:	400 V	400 V	400 V

(Subject to change)